

APE301-03

1-port Gigabit Ultra PoE Injector,
IEEE 802.3at Compliant,
Power Output 60W



Why DivioTec?

DivioTec's aim is to transcend the capabilities of the human eye and deliver an entirely new field of view. Our integrative skills and our 20 years of industry experience are constantly driving new innovations.

Our simple, easy-to-use interfaces and our rock-solid security hardware are rapidly earning the respect and confidence of our clients.

We also make a point of listening carefully to our customers' needs, applying what we learn to develop outstanding new products and a culture of exceptional service.

At DivioTec, our experience is your protection.

- 1 port Gigabit injector
- IEEE 802.3 at compliant, power output up to 60 W
- Up to 60W of PoE Power Feeding on 4-pairs
- IEEE 802.3at Compliant
- IEEE 802.3at/af backward compatible
- Compatible with IEEE 802.3af or Legacy PoE applications
- Safe on Low Power Devices Receive Only the Power They Need
- Safe and Reliable Power to WLAN Access Points
- Automatic Detection and Protection of Non-standard Ethernet Terminals
- Supports 10/100/1000Base-T LAN environment
- Compliant with CE, FCC, RoHS, safety standard EN 60950:2006

Pass Through Data Rates	10/100/1000Mbps
Pin Assignment and Polarity	1/2(-), 3/6(+), 4/5(+),7/8(-)
User Port Power	60 Watts Maximal
Input Power Voltage	100-240 VAC
Output Power Voltage	56 VDC Maximal
Indicators	System Indicator: AC Power (Green)
Connectors	RJ-45
Operating Temperature	0°C to 40°C / 32°F to 104°F
Dimensions	180 x 71 x 37 mm (7 x 2.7 x 1.4 in)
Weight	530g
Certificate	CE / FCC / safety standard EN 60950:2006
Ordering information	APE301-03-US Plug APE301-03-EU Plug APE301-03-UK Plug



2018-07-03 released
 Specifications are subject to change without notice.
 Copyright © DivioTec Inc. 2018.
 All Rights Reserved